1990 PRODUCTION SETUP									
Machine Model	Engine Model	Operating RPM±200	Production Clutch Part No.	Spring Color, Wire Dia.	Shift Wt. I.D./Gram	Bore Taper Diameter	Clutch Center Distance	Driven Helix Angle	Gearing Chain Pitch/Type
Star StarTrak	EC25PS-06	6300	1321463	Brown .200	08/47.5	1.174	12.0"	36°	Direct Drive 15/39
Sprint ES	EC34-2PM-02	6500	1321493	Brown .207	05/53.5	1.174	11.5"	36°	Direct Drive
Indy Sport, GT	EC34-2PM-03	6500	1321463 1321512	Red/White .192	10/51.7	1.174 1.160 GT	11.5"	34°	17/35
Indy Trail Super Trak	EC50PM-03	6600	1321463	Brown .200	10/51.7	1.174	12.0"	36°	21/39
Indy Trail (All)	EC50PM-01/02	7000	1321463	Red/White .192	10/51.7	1.174	12.0"	36°	21/35
Indy 400	EC40PL-02	8000	1321481	Blue 47.5	10M Blue 47.5	1.174	12.0"	34°	19/35
Indy 500 SKS Classic	EC50PL-01/02	7800	1321515 1321515 1321516	Silver .208	10M	1.174	12.0"	36°	19/35 18/35 19/35
WideTrak	EC50PL-03	7800	1321516	Red/White .192	10	1.174	12.0"	36°	19/41
650 650 SKS	EC65PL-01	7800	1321480	Gold .207	10 51.7	1.177	12.0"	34°	21/35 19/35

1990 HIGH ELEVATION RECOMMENDATIONS								
Machine Model	5000 Feet to 8000 Feet				8000 Feet to 12000 Feet			
	Shift Weight	Clutch Spring	Driven Helix	Chaincase Gearing	Shift Weight	Clutch Spring	Driven Helix	Chaincase Gearing
Star Star Trak	08	Red/White	36°	***** 15/39	08	Red/White	36°	***** 15/39
Sprint ES	05	Blue	36°	*****	06	Blue	36°	*****
Indy Sport, GT	10	Gold	34°	17/35	10 or 10M Blue	Blue or Gold	34°	17/35
SuperTrak	10M	Red/White	36°	21/39	10M Blue	Red/White	36°	21/39
Indy Trail (All)	10M	Red/White	36°	21/35	10M Red	Red/White	36°	21/35
Indy 400	10M Red	Blue	34°	19/35	10M Red	Blue	34°	19/35
Indy 500 500 SKS	10M Blue	Blue	36°	19/35 18/35	10M Blue	Blue	36°	19/35 18/35
WideTrak	10M Blue	Red/White	36°	19/41	10M White	Red/White	36°	19/41
650 650 SKS	10M Blue	Blue	34°	21/35 19/35	10M White	Blue	34°	21/35 19/35

TORQUE-O-MATIC DRIVE
Data

1991 PRODUCTION SETUP									
Machine Model	Engine Model	Operating RPM±200	Production Clutch Part No.	Spring Color, Wire Dia.	Shift Wt. I.D./Gram	Bore Taper Diameter	Clutch Center Distance	Driven Helix Angle	Gearing Chain Pitch/Type
StarLite	EC25PS-07	6300	1321514	Brown .200	08/47.5	1.174	12.0"	36°	Direct Drive
Indy Lite	EC34-2PM-03	6500	1321513	Brown .200	10/51.7	1.174	11.5"	36°	Direct Drive
Indy Sport, GT	EC44-3PM-01	6800	1321507	Red/White .192	10/51.7	1.174 1.160 GT	11.5"	36°	16/35
Indy Trail Super Trak	EC50PM-03	6600	1321498	Brown .200	10/51.7	1.174	12.0"	36°	21/39
Indy Trail (All)	EC50PM-01/02	7000	1321461	Red/White .192	10/51.7	1.174	12.0"	36°	21/35
Indy 400	EC40PL-02/04	8000	1321459	Blue .207	10M Blue/ 47.5	1.174	12.0"	34°	19/35
Indy 500 SKS/SP Classic	EC50PL-01/0204/05	7800	1321502 1321502 1321501	Silver .208	10M	1.174	12.0"	36°	19/35 18/35 19/35
WideTrak	EC50PL-06	7000	1321508	Red/White .192	10	1.174	12.0"	36°	19/41
650/RXL RXL SKS	EC65PL-02/03	7800	1321517	Gold .207	10AL 53	1.177	12.0"	36°	21/35 19/35

1991 HIGH ELEVATION RECOMMENDATIONS								
Machine Model	5000 Feet to 8000 Feet				8000 Feet to 12000 Feet			
	Shift Weight	Clutch Spring	Driven Helix	Chaincase Gearing	Shift Weight	Clutch Spring	Driven Helix	Chaincase Gearing
StarLite	08	Red/White	36°	***** 15/39	08	Red/White	36°	*****
Indy Lite	05	Blue	36°	*****	06	Blue	36°	*****
Indy Sport, GT	10	Gold	36°	17/35	10 or 10M Blue	Blue or Gold	36°	17/35
SuperTrak	10M	Red/White	36°	21/39	10M Blue	Red/White	36°	21/39
Indy Trail (All)	10M	Red/White	36°	21/35	10M Red	Red/White	36°	21/35
Indy 400	10M Red	Blue	34°	19/35	10M Red	Blue	34°	19/35
Indy 500 500 SKS	10M Blue	Blue	36°	21/39 18/35	10M Blue	Blue	36°	21/39 18/35
WideTrak	10M Blue	Red/White	36°	19/41	10M White	Red/White	36°	19/41
650/RXL RXL SKS	10M Blue	Blue	36°	21/35 19/35	10M White	Blue	36°	21/35 19/35

1992 PRODUCTION SETUP									
Machine Model	Engine Model	Operating RPM ± 200	Production Clutch Part No.	Spring Color, Wire Dia.	Shift Wt. I.D./Gram	Bore Taper Dia.	Clutch Center Distance	Driven Helix Angle & Location	Chaincase Gearing
StarLite	EC25PS-07	6300	1321514	Orange .196	10M Red	1.160	11.50"	36° B-2	Direct Drive 5 Tooth
Indy Lite Lite Deluxe	EC34-2PM-0302	6500	1321513 1321552	Gold .207	10	1.160	10.625"	36° B-2	Direct Drive 6 Tooth
Indy Lite GT	EC34-2PM-04	7000	1321507	Red/ White .192	10MB	1.160	11.03"	36° B-2	16:39
Sport 440 Sport 440 GT	EC44-3PM-01	6800	1321523	Brown .200	10	1.160	12.00"	36° B-2	16:35 16:39
Trail Trail Deluxe	EC50PM-01 /02	7000	1321539 1321540	Red/ White .192	10	1.174	12.00"	36° #2	21:39
SuperTrak	EC50PM-03	6600	1321541	Brown .200	10	1.174	12.00"	36° #2	21:39
WideTrak	EC50PL-06	7000	1321545	Brown .200	10	1.174	12.00"	36° #2	19:41
440 Indy	EC50PL-02	7800	1321547	Blue	10 MB Bushed	1.174	12.00"	34° #2	21:39
440 XCR	EC50PL-01	8000	1321547	Blue	10 MB Bushed	1.174	12.00"	36° #2	21:39
Indy 500 Classic	EC50PL-04 /05	7800	1321543 1321544	Gold	10 M Bushed	1.174	12.00"	36° #2	21:39 20:39
500 SP EFI 500 SKS	EC50PL-07	7800	1321543	Gold	10 M Bushed	1.174	12.00"	36° #2	21:39 20:39
Indy 650	EC65PL-02	8000	1321546	Blue	10 AL Bushed	1.177	12.00"	36° #2	20:35
RXL RXL SKS	EC65PL-03	8000	1321546	Blue	10 AL Bushed	1.177	12.00"	36° #2	20:35 21:39